Supplementary Material 2

This supplementary material presents methods and results of analysis of the correlations between four haemodynamic parameters and clinical treatment outcomes through use of a binary logistic regression model.

Method:

A binary logistic regression model was constructed to evaluate the relationship between flow-diversion outcome (i.e. aneurysm occlusion) and each of the four haemodynamic parameters — IR, EL, AAV, and WSS. Calibration of the model (i.e. statistical precision) was assessed by the Hosmer-Lemeshow goodness-of-fit test, with p > 0.05 being an indication of that the model has a high predictive ability (i.e. no statistical difference between observed and expected values). All analyses were performed using MedCalc version 19.1 (Ostend, Belgium).

Results:

Figure S2-1 shows the logistic regression curves corresponding to the four haemodynamic parameters investigated, and **Table S2-1** presents the statistical results of each analysis. Logistic regression analyses revealed that IR (OR: 0.9468, 95% CI: 0.8976 to 0.9987, p = 0.0208) and EL (OR: 0.9389, 95% CI: 0.8766 to 1.0057, p = 0.0171) better predict aneurysm occlusion, in contrast to AAV (p = 0.2628) and WSS (p = 0.8075), which is in agreement with the findings of our meta-analysis.




Figure S2-1. Binary logistic regression curves of IR, EL, AAV, and WSS in relation to the clinical outcomes after flow-diversion intervention. IR: inflow rate; EL: energy loss; AAV: intra-aneurysmal average velocity; and WSS: wall shear stress.

Table S2-1. Statistical results of the logistic regression of four haemodynamic parameters.

Parameters	Coeff.	SE	Wald	p value	Hosmer & Lemeshow test		ΟP	95% CL of OR
					χ^2	p value	OR	95% CI 0I OK
IR	-0.0546	0.0272	4.0292	0.0208†	6.3114	0.5039	0.9468	0.8976 to 0.9987
EL	-0.0630	0.0350	3.2324	0.0171^{\dagger}	7.6540	0.3641	0.9389	0.8766 to 1.0057
AAV	-0.0221	0.0204	1.1749	0.2628	15.7943	0.0454^{\dagger}	0.9781	0.9397 to 1.0180
WSS	0.0099	0.0407	0.0592	0.8075	7.3651	0.1178	1.0100	0.9325 to 1.0939

IR: inflow rate; EL: energy loss; AAV: intra-aneurysmal average velocity; WSS: wall shear stress; Coeff.: coefficient; SE: standard error; OR: odds ratio; and CI: confidence interval.

[†] suggestive of statistical significance (p < 0.05).